



Essential LED Panel RC035

RC035B LED40S/865 120-277 W59L59 LA

Power supply unit (On/Off), White

The Essential LED Panel is the most cost-effective LED solution, offering qualified and reliable lighting in work areas, with an extended life cycle, creating a brighter and healthier office environment.

Warnings and Safety

- For indoor use only
- The luminaire must not be used or stored in a corrosive environment where hazardous material such as sulfur, chlorine, etc. is present

Product data

General Information		Inrush time		0.03 ms
Light source replaceable	No	Power Consumption	40 W	
Driver included	Yes	Power Factor (Fraction)	0.9	
Light Technical		Connection	Flying leads/wires	
Luminous Flux	4,000 lm	Cable	Cable without plug 3-pole	
Correlated Color Temperature (Nom)	6500 K	Temperature		
Luminous Efficacy (rated) (Nom)	100 lm/W	Ambient temperature range	+10 to +35 °C	
Color rendering index (CRI)	≥80	Controls and Dimming		
Operating and Electrical		Dimmable	No	
Input Voltage	120 to 277 V	Driver/power unit/transformer	Power supply unit (On/Off)	
Line Frequency	50 to 60 Hz	Constant light output	No	
Inrush current	12.6 A			

Essential LED Panel RC035

Mechanical and Housing	
Housing Material	Steel
Housing Color	White
Overall length	595 mm
Overall width	595 mm
Overall height	33 mm
Dimensions (Height x Width x Depth)	33 x 595 x 595 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)	
Median useful life L70B50	30,000 hour(s)
Product Data	
Order product name	RC035B LED40S/865 120-277 W59L59 LA
Full product name	RC035B LED40S/865 120-277 W59L59 LA
Full product code	872016950063199
Order code	911401897384
Material Nr. (12NC)	911401897384
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169500631
Numerator - Packs per outer box	6
EAN/UPC - Case	8719514961777

